



KAMSONS CHEMICALS PVT. LTD.

TEXTURE COATINGS & ROOF POINTING COMPOUNDS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL 298 FCX	CROSSLINKED STYRENE ACRYLIC EMULSION	TEXTURE & ROOF POINTING FAST CURE	19° C	48%±2
KAMICRYL 18 FCX	CROSSLINKED ALL ACRYLIC EMULSION	TEXTURE & ROOF POINTING FAST CURE	18° C	48%±2
KAMICRYL EWR 2700	FLEXIBLE CROSSLINKED FASTCURE STYRENE ACRYLIC	TEXTURE & ROOF POINTING EARLY WATER RESISTANCE	-13° C	48%±2
KAMICRYL EWR 1400	FLEXIBLE CROSSLINKED FASTCURE PURE ACRYLIC	TEXTURE & ROOF POINTING EARLY WATER RESISTANCE	-11° C	48%±2
KAMICRYL 297 LV	GENERAL PURPOSE STYRENE ACRYLIC EMULSION	TEXTURE & PAINT COATING	18° C	50%±2

ELASTOMERIC & WATERPROOFING COATINGS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMHYB 1466	PURE ACRYLIC CROSSLINKING HYBRID EMULSION	WATERPROOFING COATINGS FOR PONDING CONDITIONS	-20° C	46%±2
KAMHYB 2 SC HYB	PURE ACRYLIC HYBRID EMULSION	EXTERIOR MEMBRANES. COMPLIES AUSTRALIAN CSIRO AS4858 CLASS III WET AREA WATERPROOFING STANDARD	1° C	50%±2
KAMTHANE RAR THX	PURE ACRYLIC CROSSLINKING HYBRID EMULSION	ARCHITECTURAL EXTERIOR HIGH BUILD ELASTOMERIC COATINGS	-22° C	47%±2
KAMICRYL 504	STYRENE ACRYLIC CROSSLINKING EMULSION	ARCHITECTURAL INTERIOR HIGH BUILD ELASTOMERIC COATINGS	-15° C	55%±2
KAMFLEX 300 HYB	STYRENE ACRYLIC HYBRID EMULSION	INTERIOR MEMBRANES. COMPLIES AUSTRALIAN CSIRO AS4858 CLASS III WET AREA WATERPROOFING STANDARD	-8° C	49%±2
KAMFLEX 500 HYB	ACRYLIC URETHANE EMULSION	EXTERIOR / INTERIOR TOUGH WATERPONDING COATINGS	-12° C	50%±2



KAMSONS CHEMICALS PVT. LTD.

MISCELLANEOUS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMPERSE OR 25	SODIUM POLYACRYLATE	DISPERSING AGENT SOLUTION	N/A	25%±2
KAMICRYL 5360	ACRYLIC THICKNER	VISCOSITY MODIFIER	N/A	25%±2
KAMHYB PU 88	PU THICKNER	VISCOSITY MODIFIER	N/A	25%±2
KAMHYB PU 200	PU THICKNER	VISCOSITY MODIFIER	N/A	25%±2
KAMWAX WB 26	PARAFFIN WAX EMULSION	PAPER & BOARD INDUSTRY	N/A	25%±2
KAMWAX WB 40	HYBRID WAX EMULSION	PAPER, PAINT & COATING INDUSTRY	N/A	40%±2
KAMWAX PE 352	POLYETHYLENE WAX EMULSION	COATING & PAINT INDUSTRY	N/A	35%±2
KAMWAX PP 422	POLYPROPYLENE WAX EMULSION	COATING & PAINT INDUSTRY	N/A	38%±2
KAMCOAT BC 27	READY BARRIER COAT	OIL & GREASE RESISTANCE	N/A	N/A
KAMCOAT BC 44	READY BARRIER COAT	MVTR & WATER RESISTANCE	N/A	N/A



KAMSONS CHEMICALS PVT. LTD.

Exploiting the Power of Polymers.....

Registered Office : Suite No. 1003, 10th Floor, Embassy Chambers, 3rd Road, Khar (W), Mumbai- 400052. Maharashtra, India

Phone : +91-22-4202 9999 (50 Lines)

E-mail : response@kamsons.com / info@kamsons.net

Website : www.kamsons.com



KAMSONS CHEMICALS PVT. LTD.

ISO 9001:2008 CERTIFIED COMPANY



Exploiting the Power of Polymers.....

KAMSONS CHEMICALS PVT. LTD.

CONCRETE MODIFICATIONS & ADMIXTURES

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL 1465	PURE ACRYLIC CROSSLINKING EMULSION	HIGH TENSILE FLEXIBLE CONCRETE MODIFICATION	-19°C	50%±2
KAMICRYL 78	PURE ACRYLIC APEO FREE EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE	18°C	48%±2
KAMICRYL 400	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE FLEXIBLE CONCRETE MODIFICATION	-8°C	57%±2
KAMICRYL 7504	STYRENE ACRYLIC CROSSLINKING EMULSION	HIGH TENSILE FLEXIBLE CONCRETE MODIFICATION	-15°C	50%±2
KAMICRYL 296	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE	20°C	50%±2

SELF PRIMING DIRECT TO CONCRETE COATINGS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMHYB 3120	ACRYLIC URETHANE HYBRID	CLEAR CONCRETE SEALERS	N/A	42%±2
KAMCRYL 340 CC	PURE ACRYLIC	CLEAR CONCRETE SEALERS	36°C	48%±2
KAMHYB PC 4601	POLYCARBONATE URETHANE ACRYLIC HYBRID	CLEAR CONCRETE SEALERS	N/A	36%±2
KAMHYB PC 4650	POLYCARBONATE URETHANE ACRYLIC HYBRID	PIGMENTED CONCRETE PAINT	N/A	36%±2
KAMICRYL 31 SC HG	ACRYLIC EMULSION	NANO CONCRETE PRIMER	35°C	47%±2
KAMHYB PC 612	SILICONE MODIFIED POLYCARBONATE URETHANE ACRYLIC HYBRID	WATER REPELLENT SELAER FOR SANDSTONE & MASONARY	N/A	35%±2

KAMSONS CHEMICALS PVT. LTD.

SELF CROSSLINKING COATINGS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL 2 ST ZX	SELF CROSSLINKING STYRENE ACRYLIC EMULSION	EXTERIOR FLEXIBLE COATING FOR WOOD & FACADES	11°C	55%±2
KAMICRYL 12 SC ZX	SELF CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR FOR TIMBER & WALL COATINGS	14°C	50%±2
KAMICRYL 24 SC ZX	SELF CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & FACADES	24°C	50%±2
KAMICRYL 35 SC ZX	SELF CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & VARIOUS SUBSTRATES	37°C	50%±2
KAMICRYL 48 SC ZX	SELF CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & FACADES	44°C	50%±2
KAMICRYL 63 SCX	ACRYLIC CROSSLINKING EMULSION	HIGH GLOSS ENAMELS	43°C	48%±2

ADVANCED SPECIALITY ARCHITECTURAL COATINGS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL PR C18	ALL ACRYLIC EMULSION	SUPERIOR STAIN RESISTANCE/ METAL ADHESION. EXTERIOR & INTERIOR COATINGS	16°C	52%±2
KAMICRYL PR C25	ALL ACRYLIC EMULSION	SUPERIOR STAIN RESISTANCE/ METAL ADHESION. EXTERIOR & INTERIOR COATINGS	24°C	52%±2
KAMICRYL PR C35	ALL ACRYLIC EMULSION	SUPERIOR STAIN RESISTANCE/ METAL ADHESION. EXTERIOR & INTERIOR COATINGS	36°C	52%±2
KAMICRYL STR C26	STYRENE ACRYLIC EMULSION	SUPERIOR STAIN RESISTANCE/ METAL ADHESION. INTERIOR COATINGS	23°C	50%±2
KAMICRYL PR CX15 HYB	ACRYLIC URETHANE HYBRID EMULSION	SUPERIOR COATINGS. EXCELLENT STAIN RESISTANCE/ METAL ADHESION	20°C	50%±2
KAMICRYL FPR 320 E	FLEXIBLE ACRYLIC EMULSION	EXTERIOR COATINGS. GOOD STAIN RESISTANCE/ METAL ADHESION	<0°C	50%±2

TIMBER COATINGS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL TM 14	ALL ACRYLIC EMULSION	EXTERIOR TIMBER & DECKING COATING EMULSION	15°C	50%±2
KAMICRYL TM 15 WX	ACRYLIC WAX MODIFIED HYBRID EMULSION	WATER REPELLENT TIMBER COATINGS	11°C	42%±2
KAMICRYL HYB S-18	SILICONE MODIFIED URETHANE ACRYLIC HYBRID EMULSION	HIGHLY DURABLE WATER REPELLENT TIMBER COATING	22°C	42%±2
KAMICRYL UM 19	URETHANE ALL ACRYLIC EMULSION	TANNIN BLOCKING	18°C	45%±2

GRAPHIC ARTS, OVERPRINT VARNISH & INKS

PRODUCT DESCRIPTION	TYPE	APPLICATION RECOMMENDATIONS	TG	SOLIDS
KAMICRYL 2090	HARD STYRENE ACRYLIC NON FILM FORMING EMULSION	HIGH OPTICAL CLARITY & GLOSS. FAST DRY. GOOD HEAT RESISTANCE	110°C	44%±2
KAMICRYL 2017	STYRENE ACRYLIC FILM FORMING EMULSION	WATER BASED FLEXOGRAPHIC AND GRAVURE PRINTING INKS.	7°C	48%±2
KAMICRYL 2074 OR	FLEXIBLE STYRENE ACRYLIC FILM FORMING EMULSION	FLEXO AND GRAVURE INKS ON FLEXIBLE PLASTIC FILM & FOIL.	-9°C	48%±2
KAMICRYL 361	STYRENE ACRYLIC WITH GOOD HIDING POWER & OPACITY PROPERTIES. FAST DRYING	FOR PAPER & LOW COST CORRUGATED INKS. IMPROVES TRANSFER & HIDING POWER.	75°C	50%±2
KAMICRYL OPV HG 8000	READY WATER BASED OPV	ULTRA HIGH GLOSS	N/A	N/A
KAMICRYL OPV GL 60	READY WATER BASED OPV	GENERAL PURPOSE GLOSS	N/A	N/A
KAMICRYL OPV SATIN 30	READY WATERBASED OPV	SATIN VARNISH	N/A	N/A
KAMICRYL OPV MATT 15	READY WATERBASED OPV	MATT VARNISH	N/A	N/A
KAMPRILL 50 S	LOW MW STYRENE ACRYLIC	HIGH SOLIDS SOLUTION	85°C	50%±2
KAMPRILL 33 S	HIGH MW STYRENE ACRYLIC	HIGH MW SOLUTION	99°C	33%±2
KAMICRYL 5390	ALKALI SOLUBLE ACIDIC EMULSION	GOOD GRINDING PROPERTIES & COLOUR ACCEPTANCE. GOOD LET DOWN VEHICLE	N/A	42%±2