

KAMSONS CHEMICALS PVT. LTD.

Plot No. A-726, T.T.C. Industrial Area, Village Mahape, Thane Belapur Road, Dist. Thane, Navi Mumbai. INDIA.

Ph: (91)22-26854728, (91)22-26854808. Fax: (91)22-26854438

KAMICRYL - 5010 Thermoplastic Acrylic Resin

Kamicryl-5010 is an Co-polymer of various Acrylic Monomers available in free flowing solids and solution form.

These are extensively used in the formulation of Lacquers and speciality coatings.

Kamicryl-5010 shows the following characteristics:

- Outstanding weatherability and resistance to ultra violet degradation
- Water clear transparency
- High gloss, hardness and adhesion to various substrates like metals, plastics, wood, concrete
- Excellent resistance to water, alcohols, oils, solvents, chemical fumes, dilute acids, alkalies

Product

Specification: Solid content : $46 \pm 1\%$ in toulene

Viscosity at 30 °C : 5-10 poise

Brookfield RVT Sp.3

20rpm (30% Solution in Toulene)

Acid Value : 3 - 7

(mgm KOH/gm)

Properties Of Film : Tough, durable film

Typical Applications:

- Hard but flexible coatings/paints for vinyl plastics and Polystyrene surfaces
- Upgrading of alkyd based synthetic enamels and marine paints
- Automotive finishes and refinishes
- Metal decoration coatings and lacquers
- Concrete coatings and sealants