



KAMSONS CHEMICALS PVT. LTD.

Plot No. A-726, T.T.C. Industrial Area, Village Mahape,
Thane Belapur Road, Dist. Thane, Navi Mumbai-400705. INDIA
Ph : (91)22-26854728, (91)22-26854808. Fax : (91)22-26854438

Technical Data Sheet

Kamicryl-2038

RESIN SOLUTION

Low Molecular Weight Polyelectrolyte solution based on Styrene-Acrylic Acid Copolymer, with excellent Pigment Wetting and good Resolubility for pigment dispersion, fluid inks, and overprint varnishes.

Typical Properties :

Appearance	:	Light Amber Clear Emulsion
Non-Volatiles	:	32.0 ± 1 %
pH	:	8 ± 0.5
Molecular Weight, Mw	:	8500
Acid Number (NV)	:	215
Glass Transition Temp., °C (Tg)	:	85
Density (gms/cc)	:	1.06
Freeze / Thaw stable	:	Yes

Suggested Applications :

High Gloss Water Based Flexographic and Gravure printing inks, Over Print Varnish, functional coatings for paper and board.

THESE SUGGESTIONS & DATA ARE BASED ON INFORMATION, WE BELIEVE TO BE RELIABLE. THEY ARE OFFERED IN GOOD FAITH, BUT WITHOUT GUARANTEE, AS CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL.
